Connecting the TH100

Connecting to TV-SET with HDMI connector



Connecting to TV-SET with 3,5mm AV connector



Connecting to audio system with SPDIF connector



IPTV SET TOP BOX INSTRUCTION MANUAL



Technical Specifications

Audio output S/PDIF, HDMI 1.4-output, Composite + stereo A/V output, Ethernet 100 Mb/s, 2 x USB 2.0, WiFi (optional)
Local network PC or NAS, Stream media protocols (RTSP, RTP, UDP, IGMP, HTTP), USB-device
Video modes: 1080i, 1080p, 720p, 576p, 480p, PAL, NTSC Video codecs: MPEG1/2, H.265, H.264, MPEG4 part 2, XviD; HD video supporting Audio codecs: MPEG-1 layer I/II, MPEG-2 layer II MPEG-2 layer III (mp3)
Power; Remote Activity; LAN Link/Activity
2,5 Watts (Max), 200mA/12V
External power adapter DC 12V
Operating Temperature: 10°C~30°C Operating Humidity : 10%~80% (Non-Condensing)
130mm(L) x 88mm(W) x 28mm(H)

Setting up the unit

- 1. Plug in the HDMI cable if not HDMI cable is detected the AV output will be used
- 2. Plug in the power (IMPUKIANT II DO NO FINE)
 3. Wait until you see a message of NO CONNECTION


 3. Wait until you see a message of NO CONNECTION

 4. The remote control -2. Plug in the power (IMPORTANT!! Do not plug in the network)

- 5. Plug in the network cable
- 6. Press the Keyboard on the remote control to see the onscreen keyboard
- 7. Input the portal and network settings
- 8. If needed change the name of the device it will report to the portal
- 9. Press F2 of the remote control
- 10 Press F4 of the remote control

Package Contents:

IPTV Set top box -1pcs **External Power Supply** -1pcs IR Remote control -1pcs AAA batteries -2pcs Instruction manual -1pcs HMDI cable -1pcs



USING THE REMOTE CONTROL UNIT

The remote control included into the package needs two AAA batteries (also included into the package*) to operate.

Inserting the batteries







Remove battery cover

Insert two AAA batteries

Replace the battery cover

Programmable Remote Control Unit

TH100 package includes a remote control with a group of five programmable buttons, marked with blue color which may be used to control other devices.

To program the buttons:

Press and hold the blue "On/Off" and the "A/V" buttons at the same time until you notice the red light of he blue "On/Off" button becomes brighter. This means the remote is ready to

- 1. Choose the button you want to "teach" a new code to the red light of the "On/Off" button will start to blink.
- 2. Place the infrared outputs of the two remotes against each other and press the button on the remote control of the other device that you wish to copy and hold for 2 seconds.
- 3. You sill see the blue "On/Off button blink a couple of times quickly, this means the button has been programmed.
- 4. Repeat steps 1 to 3 to choose and program the other buttons of the remote control
- 5. Press and hold the blue "On/Off" and the "A/V" buttons at the same time until you notice the red light of he blue "On/Off" button turns off to save the programmed data.













